

Automatic standing basin tap, DC power

product cod: FAN7035MIXC

category: Categories > Sanitary fittings



faneco

Manufacturer: Faneco

QR code:



Body's material: Chrome plated brass
Purpose: For cold or mixing hot and cold water
Launch: Automatic - photocell
Minimal start distance: 0,5 - 10 cm
Voltage: DC 110 - 220 V, 50 - 60 Hz
Water pressure: 0,5 - 6 bar
Standard water flow at 3 bars: 40l / min.
Maximum temperature: 80°
Connection: 1/2"

Additional functions:

- Water flow capacity adjustment: 6l/min., 5l/min., 8l/min.
- Water outflow blockage after 3 seconds of removing hands

Elements included:

- Spout equipped with a vandalproof strainer
- Tap
- Stainless steel braided flexible hose
- Basin mounting kit

Features:

- Excellent physical damage resistance due to the highest quality materials
- Simple operation
- Easy mounting

Dimensions (spout): Height 141 mm, width 60 mm, depth 130 mm

Individual packaging dimensions: Height 380 mm, width 70 mm, depth 140 mm

Weight (1 piece): 1,38 kg

Individual packaging weight: 1,46 kg

Quantity in package: 8 pcs.

Multipackaging dimensions: Height 300 mm, width 400 mm, length 420 mm

Multipackaging weight: 12,5 kg

Multipackaging volume: 0,05 m³

Certificate: WRAS

Waterproof: IP65

Warranty: 2 years "door-to-door", excluding consumable parts